

MAXWAY 10W-40

Diesel engine oil of SHPD quality

Product description

MAXWAY 10W-40 is a semi-synthetic diesel engine oil of SHPD quality (Super High Performance Diesel) for vehicles in heavy traffic.

Application areas

MAXWAY 10W-40 is recommended for excellent performance in all types of diesel engines, even under demanding conditions. The oil can be used to gain extended drain intervals. The product is recommended as a universal oil when you have many different types of diesel engines that require different oil specifications. It also works well in petrol engines.

Characteristics and advantages

Satisfies the high demands that leading engine manufacturers prescribe. Lower maintenance costs and high vehicle availability through extended drain intervals. Excellent protection, effective soot control and cleaning properties increase engine life and reduce wear. Gives lower fuel consumption compared to SAE 15W-40 oils. Good cold starting properties provide good engine protection and reduced wear, even at low temperatures. Universal oil for trucks, buses and light vans. Approved for both diesel and petrol engines.

Tests and approvals

Specifications: ACEA E7-10, API CI-4, API SL

Approvals: MB-Approval 228.3, Volvo VDS-3, MAN M 3275-1, SISU Diesel TIER 3, CAT ECF-1a, CAT ECF-2 CES 20076, CES 20077, Renault VI RLD, Renault VI RLD-2, Scania LDF-2, MTU Type 2, Mack EO-M+, Mack EO-N, Deutz DQC-III-10

Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available on www.statoillubricants.com or supplied on request.

Typical Data

Characteristics	Typical value	Unit	Method
CCS at -25°C	6202	mPas	ASTM D 5293
Density at 15°C	870	kg/m ³	ISO 12185
Flash point COC	230	°C	ISO 2592
HT/HS	4.0	mPas	CEC L-36-A-90
Pour point	-42	°C	ISO 3016
TBN	9.0	mg KOH/g	ASTM D 2896
Viscosity at 40°C	95	mm ² /s	ISO 3104
Viscosity at 100°C	14.3	mm ² /s	ISO 3104
Viscosity index	162	-	ISO 2909

Revision date 19-Aug-2014