

# MAXWAY 15W-40

Diesel engine oil of SHPD quality

## Product description

MAXWAY 15W-40 is a diesel engine oil of SHPD quality (Super High Performance Diesel) for vehicles in heavy traffic.

## Application areas

MaxWay 15W-40 is recommended for excellent performance in all types of diesel engines, even under demanding conditions. The oil can be used to gain extended drain intervals. The product is recommended as a universal oil when you have many different types of diesel engines that require different oil specifications. It also works well in petrol engines.

## Characteristics and advantages

Satisfies the high demands that leading engine manufacturers prescribe. Lower maintenance costs and high vehicle availability through extended drain intervals. Excellent protection and performance extend engine life. Effective soot control and cleaning properties reduce engine wear. Universal oil for trucks, buses and light vans. Approved for both diesel and petrol engines.

## Tests and approvals

Specifications: ACEA E7-10, ACEA A3/B3-10, API CI-4, API SL, CAT ECF-1a, CAT ECF-2, Mack EO-M+, Renault VI RLD, Renault VI RLD-2

Approvals: MB-Approval 228.3, Volvo VDS-3, SISU Diesel TIER 3, CES 20076, CES 20077, MAN M 3275-1, MB-Approval 229.1

MTU Type 2, Deutz DQC-III-10

## Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available on [www.statoillubricants.com](http://www.statoillubricants.com) or supplied on request.

## Typical Data

Characteristics	Typical value	Unit	Method
CCS at -20°C	6980	mPas	ASTM D 5293
Density at 15°C	884	kg/m <sup>3</sup>	ISO 12185
Flash point COC	210	°C	ISO 2592
HT/HS	4.0	mPas	CEC L-36-A-90
Pour point	-36	°C	ISO 3016
TBN	9.3	mg KOH/g	ASTM D 2896
Viscosity at 40°C	102	mm <sup>2</sup> /s	ISO 3104
Viscosity at 100°C	14.5	mm <sup>2</sup> /s	ISO 3104
Viscosity index	147	-	ISO 2909

Revision date 19-Aug-2014