

# STATOIL LAZERWAY LL 5W-30

## Motor Oil

### APPLICATIONS

LazerWay LL 5W-30 is a modern, fully synthetic engine oil specially developed for extended oil change intervals in some VW models.

### ADVANTAGES

LazerWay LL 5W-30 provides the opportunity for twice as long oil change intervals in VW/Audi engines. The product ensures optimum lubrication at all operating temperatures and extremely good cold start properties in cold conditions. The low viscosity facilitates large reductions in fuel consumption. The excellent wear protection gives a long engine lifetime.

### CHARACTERISTICS

LazerWay LL 5W-30 is an engine oil based on the very latest longlife technology. The product satisfies the demands of the VW standards 504.00 and 507.00

LazerWay LL 5W-30 has undergone comprehensive testing on the test-bench and extensive field tests in test vehicles, in order to guarantee the extended oil-change intervals.

### TYPICAL INSPECTIONS

| CHARACTERISTICS     | METHODS       | UNITS              |       |
|---------------------|---------------|--------------------|-------|
| SAE-class           | -             | -                  | 5W-30 |
| Density at 15 °C    | ASTM D 4052   | kg/m <sup>3</sup>  | 849   |
| Viscosity at 40 °C  | ASTM D 445    | mm <sup>2</sup> /s | 70    |
| Viscosity at 100 °C | ASTM D 445    | mm <sup>2</sup> /s | 11,6  |
| CCS at -30 °C       | ASTM D 5293   | mPa.s              | 6130  |
| Viscosity index     | ASTM D 2270   | -                  | 163   |
| Flash point COC     | ASTM D 92     | °C                 | 240   |
| HTHS                | CEC L-36-A-90 | mPas               | >3,5  |
| Pour point          | ASTM D 97CEC  | °C                 | -45   |

### TESTS AND APPROVALS

VW 504.00/507.00, ACEA A3/B4, ACEA C3, BMW LL-04, MB-Approval 229.51 (31) LazerWay LL 5W-30 to be used where VW 503.00, 506.00 and 506.01 is recommended

The right to change product specifications is reserved.

### HANDLING AND STORAGE

Avoid skin contact.  
Repeated contact with used motor oil may cause severe skin damage.  
Dispose of used oils properly.  
Safety data sheet available for professional user on request.



Statoil Lubricants, 118 88 Stockholm.

Customer service tel 08-429 68 50, fax 08-429 68 51, email: smobest@statoil.com

2009-04-28

*Friction Fighters™*

