

STATOIL TRANSWAY PS DX III

Automatic transmissions

APPLICATIONS

TransWay PS DX III is semi synthetic fluid recommended for automatic transmissions and manual gearboxes for which ATFs are prescribed. This product is also recommended for older transmissions that call for DX IID or IIE. It is also suited for some hydraulic transmissions, servo control mechanisms, hydraulic systems, etc.

ADVANTAGES

TransWay PS DX III is the latest generation ATF and meets multiple specifications, such as Dexron III and Ford Mercon. This product thus covers a broad use with improved performance features. This means that gearboxes will work better and more reliably, and that the fluid need not be changed as often.

CHARACTERISTICS

The new DX III specification signifies improvements over the older DX fluids. TransWay PS DX III exhibits a better friction characteristic over extended periods of time and over a broader temperature range, is more oxidation-stable and has better low-temperature characteristics.

The end result is improved automatic transmission reliability and performance. The service life of the fluid and drain intervals are extended.

TYPICAL INSPECTIONS

CHARACTERISTICS	METHODS	UNITS	
Density at 15 °C	ASTM D 4052	kg/m ³	850
Viscosity at 40 °C	ASTM D 445	mm ² /s	36
Viscosity at 100 °C	ASTM D 445	mm ² /s	7,5
Brookf. Visc. at -40 °C	ASTM D 2983	mPa.s	<18100
Viscosity Index	ASTM D 2270	-	209
Pour Point	ASTM D 97	°C	-53
Flash Point COC	ASTM D 92	°C	200

TESTS AND APPROVALS

API GL-4, Volvo 97341, Voith 55.6335 (Former G 607) ZF TL-ML 04D/14A/17C, MAN 339 Type Z-1, MAN 339 type V1, Performance level: CAT TO-2, GM Type A-Suffix A, MB236.1, MB 236.5, Ford Mercon, Dexron III H, ZF TL-ML 02 F/09/11B/14B, Allison C-4.

HANDLING AND STORAGE

Avoid skin contact.
Wash thoroughly with soap and water, after skin contact.
Dispose of used oils properly.
Safety data sheet available for professional user on request.

The right to change product specifications is reserved.



Statoil Lubricants, 118 88 Stockholm.

Customer service tel 08-429 68 50, fax 08-429 68 51, email: smobest@statoil.com

2009-02-04

Friction Fighters™

